



WALLANTICS

INSPIRING DESIGN'S


SPORTS FLORING



www.wonderfloor.com



Bravo




Sports & Wellness Flooring

Bravo
Elite
6.50MM



Elite Red - 081



Elite Blue - 082



Elite Orange - 083

Elite grey 087



Elite Green - 084



Elite Wood - 085A



Elite Wood - 085



Bravo
4.50MM



Ace. 091, Cherry Red



Ace. 092, Blue



Ace. 093, Orange



Ace. 094, Green



Ace. 095, Neo Silver



~~ACE. 096, Yellow~~

79500






AR 051



AR 053



AR 054




AR 055



Salient Features

- Glass Fiber Tissue (GFT) reinforced for dimensional stability and strength
- PUR surface protection
- Superior shock absorbing cushion base layer
- Tough and sturdy to withstand heavy traffic and soft enough for a comfortable and jerk free workout
- Specially formulated high abrasion resistant wear layer which makes it "T" rated
- Application areas: sports courts, fitness centres, schools, yoga centers, hospitality, etc.

Bravo multiple layers for multiple benefits



WONDERFLOOR - the world-class vinyl flooring is a quality product from RMG Polyvinyl India Limited, an ISO 9001:2015 systems certified company. We are the largest manufacturer & exporter of PVC floor coverings, film, sheeting and artificial leather. We manufacture a wide range of vinyl flooring in state-of-the-art plant & machinery equipped with latest technology and optimum quality control. Wonderfloor has a wide sales distribution network across India.

Bravo is a premium cushioned sports and wellness flooring designed for modern day requirement of a floor that is heavy duty but soft enough for a comfortable and jerk free workout in a gym, sports court or a fitness centre. The high strength wear layer takes care of the heavy loads, the 'impregnated Glass Fibre Tissue' reinforcement provides a very high dimensional stability and lay flat properties to the product in any weather conditions. The densely compact cushioned base layer absorbs the jerks and also adds to the acoustical property of the floor.

PERFORMANCE CHARACTERISTICS

CHARACTERISTIC	SYMBOLS	TEST METHOD	RESULTS 4.50 MM	RESULTS 6.50 MM
THICKNESS		EN 426	4.50 MM	6.50 MM
ROLL DIMENSION		EN 426	2 mt x 15 linear mt	2 mt X 15 linear mt
TOTAL WEIGHT		EN 430	3.3 KG/SQ	4.3 KG/SQ
THICKNESS OF WEAR LAYER		EN 429	0.50 MM	1.00 MM
DIMENSIONAL STABILITY		EN 434	±0.10%	±0.10%
RESIDUAL INDICATOR AFTER STATIC LOAD		EN 433	±0.40 MM	±0.40 MM
FLEXIBILITY		EN 438	20 MM MANDREL PASSED	20 MM MANDREL PASSED
ABRASION RESISTANCE		EN 660-2 EN 549	WEAR GROUP 1	WEAR GROUP 1
SURFACE SPREAD OF FLAME		BS 476 PART 7	CLASS 1	CLASS 1
FIRE PROPAGATION		BS 476 PART 6	(I) = 10.2 (II) = 1.7 } CLASS '0',	(I) = 10.2 (II) = 1.7 } CLASS '0',
HYGIENE			TEST RESULT DEMONSTRATES THAT IT INHIBITS GROWTH OF MICROBES	TEST RESULT DEMONSTRATES THAT IT INHIBITS GROWTH OF MICROBES
COLOUR FASTNESS TO DRY LIGHT		ISO 105-B02	4-BLUE WOOL STANDARD 3	4-BLUE WOOL STANDARD 3
SLIP RESISTANCE		DN 51130	R 9	R 9
BEARING A CASTOR CHAIR		EN 425	SUITABLE/CONTINUOUS USE	SUITABLE/CONTINUOUS USE
RESISTANCE TO CHEMICALS		EN 423	NO VISIBLE CHANGE	NO VISIBLE CHANGE
SOUND ABSORPTION		ISO 140-4 EN ISO 717-2	α LW = 19dB	α LW = 24dB
PERFORMANCE CLASSIFICATION		EN 668	33, 34	33, 34
SURFACE PROTECTION			PUR	PUR

RECOMMENDATION FOR INSTALLATION

Wonderfloor sheet must be allowed to relax for 24 hours in room temperature between 18°C and 27°C prior to installation. Vinyl rolls are suitable for laying on any surface such as concrete, steel wooden floors etc. provided the sub-floor is even, hard and dry. Damp floors should be dried before the commencement of laying. Before installation, the base floor must be thoroughly clean, dry and free from grease & grit. Wonderfloor recommends use of Fevicol SR 998, Fevicol SR 505 or any other equivalent rubber/acrylic based adhesive of similar type.

MAINTENANCE

Do's: • The surface should be cleaned daily with damp mop and weekly or fortnightly with soap solution • Prevent point load indentation by covering your furniture legs with rubber stopper caps • To remove stubborn stains, rub the affected area immediately with a soft coil brush or fine steel wool soaked in a warm soap solution • Spill marks on the floor can be removed with little application of diesel • Use door coor or suitable mats to minimize accumulation of dust on Wonderfloor vinyl flooring • Use water to remove any chemical spill on flooring.

Don'ts: • Do not use any strong detergent, harsh cleaning agent or dry steel wool • Throwing of lighted cigarette butts or match sticks on the floor should be avoided as it could lead to burn marks on the floor • Do not drag any heavy object or furniture on the flooring to avoid scratches on the floor.

For institutional/bulk enquiries, please e-mail : mk@rmgpoly.com
or call : +91 9711200510

For export enquiries, please e-mail : info@rmgpoly.com or call : +91 9873138885



ISO 9001:2015
Certificate No. 81196 00117943

RMG POLYVINYL INDIA LIMITED

Corporate Office: UGSR & Ansal Plaza, Sector 1, Vasant, Okhla Industrial Estate, Gurgaon (Haryana) INDIA
Tel: +91 22 4244552-503/904-905-906, Fax: +91 22 5007679
E-mail: info@rmgpoly.com, website: www.wonderfloor.com

Regional Offices: • Ahmedabad: +91 927202999 • Bangalore: +91 934263794 • Bhubaneswar: +91 9582244009
• Chennai: +91 8383353325 • Coimbatore: +91 9422022282 • Hyderabad: +91 967795422 • Indore: +91 7832990904
• Kolkata: +91 9820668222, 9082939009 • Kochi: +91 9892185421 • Lucknow: +91 9026708007
• Mumbai: +91 9223075079 • Pune: +91 939295421 • Patna: +91 8252120000

www.rmgpoly.com, www.wonderfloor.com WONDERFLOOR is the registered Trade Mark of RMG Polyvinyl India Limited